

PY0-ZBH-300

PY0 Quick Disconnect Fitting with Zbeam® Half

PY0 Quick Disconnect Fitting with Zbeam Half allows an easy connection to Polar Focus[®] line array accessories.

This product allows for two point support of a cluster for permanent installations, with a center service pick point, with full pan control. Not for use with two hoists.

* If you need to lift your cluster with two chain hoists, you must use the PY0-ZBR, for Zbeam with Rocker Arm.

Polar Focus Ultimate Line Array Rigging.

For more assistance, call our audio rigging consultants at (413) 586-4444.



Figure 1.
Polar Focus PY0 Universal Joint Fitting with Zbeam® Half

Allows for two point support of a cluster for permanent installations with a center service pick point with full pan control.

See www.linearrayframes.com for pan control, roof attachment, OEM products, line array frames and manufacturer-specific rigging.




Architectural Specification:

The rigging device shall allow for pan control while under load. The pan control shall retain a set pan angle through the use of a rated friction bearing.

Upper rigging points shall consist of two 3/4" pad-eyes and one centrally located 1/2" eye-nut.

The rigging device shall be manufactured of welded structural steel and grade 5 hardware. It shall have a Working Load Limit of 300 lbs (136 kg) with a 10:1 design factor.

The rigging device shall be the PY0-ZBH-300.



15" (381mm) Overall Length: Overall Height: 8.7" (221mm) Overall width: 5.5" (140mm) Max. Usable length: 13" (330mm) Weight: 8.5 lbs (3.9 kg)

Primary Material: Structural Steel Finish: Powder Coat Black

Working Load Limit: 300 lbs (136 kg)



