

## PY1-ZBH-1550

## PY1 Quick Disconnect Fitting with Zbeam® Half

PY1 Quick Disconnect Fitting with Zbeam Half allows an easy connection to Polar Focus<sup>®</sup> line array accessories.

This product allows for two point support of a cluster for permanent installations, with a center service pick point, with full pan control. Not for use with two hoists.

\* If you need to lift your cluster with two chain hoists, you must use the PY1-ZBR, for Zbeam with Rocker Arm.

Polar Focus Ultimate Line Array Rigging.

For more assistance, call our audio rigging consultants at (413) 586-4444.



Figure 1.
Polar Focus PY1 Universal Joint Fitting with Zbeam® Half

Allows for two point support of a cluster for permanent installations with a center service pick point with full pan control.

See www.linearrayframes.com for pan control, roof attachment, OEM products, line array frames and manufacturer-specific rigging.



## Architectural Specification:

The rigging device shall allow for pan control while under load. The pan control shall retain a set pan angle through the use of a rated friction bearing.

Upper rigging points shall consist of two ¾" pad-eyes and one centrally located 3/4" eye-nut. The rigging device shall be manufactured of welded structural steel and grade 5 hardware. It shall have a Working Load Limit of 1550 lbs (703 kg) with a 10:1 design factor.

The rigging device shall be the PY1-ZBH-1550.

Overall Length: 20" (508mm)
Overall Height: 12.4" (315mm)
Overall width: 5.5" (140mm)
Max. Usable length: 18" (457mm)

Weight: 21.5 lbs (9.8 kg)
Primary Material: Structural Steel

Finish: Powder Coat Black

Working Load Limit: 1550 lbs (703 kg)

